

# BTT

Take advantage of smartphone-controlled, above-ground irrigation for easier access to the hose tap.

## KEY BENEFITS

- Number of zones:
  - 1 or 2 (fixed models)
- Battery-operated tap timer with Bluetooth® control
- 1 smartphone manages an unlimited number of controllers
- 1-second to 24-hour run time with 4 start times
- Cycling mode repeats continuously within user-defined water windows, perfect for drip systems or germinating seeds
- Suspend irrigation up to 99 days during the off-season, perfect for seasonal markets
- Manual push-button operation for quick operation without a smartphone
- Automatic water shutoff after 1 hour prevents water waste
- Blinking LED low-battery alert indicates battery replacement
- Alkaline batteries included for quicker installation
- Includes quick coupler adapter

## OPERATING SPECIFICATIONS

- Two 1.5V AA alkaline batteries (included)
- Flow rate: 1.9 to 2,271 L/H
- Recommended pressure: 0.5 to 8 bar (50 to 800 kPa)
- See friction loss chart
- Bluetooth 4.0/4.2 (BLE)
- Approvals: Plastic IPX6 (outdoor), UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 2 years

## APP SPECIFICATIONS

- iOS® 9.0 or above, Android™ 4.4 or above
- Maximum communication distance: 10 m
- See all app features at [hunter.info/BTT](http://hunter.info/BTT)

BTT	
Model	Description
BTT-101	1-zone Bluetooth Tap Timer, 1" BSP and 3/4" hose thread, quick coupler adapter
BTT-201	2-zone Bluetooth Tap Timer, 1" BSP and 3/4" hose thread, quick coupler adapter

BTT ACCESSORIES	
Model	Description
BTT-LOC	BTT adapter for 16-18 mm dripline
PRLG203FH3MH	1.4 bar (140 kPa) pressure regulator, 3/4" hose thread
PRLG253FH3MH	1.7 bar (170 kPa) pressure regulator, 3/4" hose thread
PRLG303FH3MH	2 bar (200 kPa) pressure regulator, 3/4" hose thread
PRLG403FH3MH	2.8 bar (280 kPa) pressure regulator, 3/4" hose thread

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG Inc. and any use of such marks by Hunter Industries is under licence. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under licence. Android is a trademark of Google LLC.



**BTT-101**  
 Inlet diameter: 3/4" and 1"  
 Outlet diameter: 3/4"  
 Height: 16.8 cm  
 Width: 12 cm  
 Depth: 6 cm



**BTT-201**  
 Inlet diameter: 3/4" and 1"  
 Outlet diameter: 3/4"  
 Height: 15.7 cm  
 Width: 13.5 cm  
 Depth: 7.6 cm



**BTT-LOC**  
 (optional)  
 Inlet diameter: 3/4"  
 Outlet diameter: 16-18 mm dripline  
 Height: 7 cm  
 Width: 3 cm




**Pressure Regulator**  
 (optional)  
 Inlet diameter: 3/4"  
 Outlet diameter: 3/4"  
 Height: 7 cm  
 Width: 4 cm

## BTT



To control drip irrigation applications with BTT, use the BTT-LOC Drip Adapter, which connects BTT to HDL surface and subsurface systems.

Compatible with:



**HDL Dripline**

Visit [hunterindustries.com](http://hunterindustries.com)